



**DIMENSIONS (Inches)**

SIZE	A	D	E	F	G	X	AA	BB	CC	DD	EE	GG	HH	WT (lbs.)	ACT MODEL
16	4.02	4	1.14	21.25	12.20	20.08	6.50	9.72	4.92	4.56	8.51	11.80	21.80	197	RS-5321-01
18	4.49	4	1.26	22.75	13.40	20.94	6.50	9.72	4.92	4.56	8.51	11.80	22.67	228	RS-5321-01
20	5.00	4	1.26	25.00	14.37	21.73	6.50	9.72	4.92	4.56	8.51	11.80	23.46	272	RS-5321-03
24	6.06	4	1.38	29.50	17.80	27.28	7.64	11.81	5.75	5.47	9.92	11.80	29.09	473	RS-6401-01
28	6.50	4	1-1/4"-8	34.00	20.08	30.59	8.78	13.78	6.34	6.73	2.52	17.72	33.00	761	RS-7041-01
30	6.50	4	1-1/4"-8	36.00	20.08	31.62	8.78	13.78	6.34	6.73	2.52	17.72	34.03	847	RS-7041-01
32	7.48	4	1-1/2"-8	38.50	22.84	32.48	8.78	13.78	6.34	6.73	2.52	17.72	34.90	986	RS-7041-01
36	7.87	4	1-1/2"-8	42.75	25.04	35.24	9.37	14.67	6.85	7.20	2.52	17.72	37.40	1,225	RS-8321-01

**DESCRIPTION:**

16"-36" API 609, 150# Wafer Body, Resilient Seated BFV with Gear and Handwheel

**DATE:**

08/13/2024

**DRAWING:**

TS-DD0012-A



McWane Plant & Industrial  
1201 Vanderbilt Road  
Birmingham, AL 35234