



DIMENSIONS (Inches)																
SIZE	A	D	E	F	G	H	J	M	N	P	R	S	T	V	Y	WT (lbs.)
2	1.70	4	5/8"-11	4.75	3.15	1.10	5.51	3.54	4	0.40	2.76	0.433	0.55	F07	M5	7
2.5	1.81	4	5/8"-11	5.50	3.50	1.10	5.90	3.54	4	0.40	2.76	0.433	0.55	F07	M5	8
3	1.81	4	5/8"-11	6.00	3.74	1.10	6.22	3.54	4	0.40	2.76	0.433	0.55	F07	M5	10
4	2.05	8	5/8"-11	7.50	4.49	1.10	6.93	3.54	4	0.40	2.76	0.433	0.60	F07	M5	16
5	2.20	8	3/4"-10	8.50	5.00	1.10	7.48	3.54	4	0.40	2.76	0.551	0.60	F07	M5	21
6	2.20	8	3/4"-10	9.50	5.47	1.10	8.35	3.54	4	0.40	2.76	0.551	0.60	F07	M5	24
8	2.36	8	3/4"-10	11.75	6.89	1.38	9.25	5.90	4	0.55	4.92	0.669	0.63	F12	M8	43
10	2.68	12	7/8"-9	14.25	7.99	1.38	10.43	5.90	4	0.55	4.92	0.866	0.63	F12	-	68
12	3.07	12	7/8"-9	17.00	9.53	1.38	12.00	5.90	4	0.55	4.92	0.866	0.70	F12	-	97
14	3.07	12	1"-8	18.75	10.51	1.38	14.49	5.10	4	0.55	4.92	0.866	0.55	F12	-	120
16	4.02	16	1"-8	21.25	12.16	1.42	15.75	6.89	4	0.70	5.51	1.063	0.55	F14	-	185
18	4.49	16	1-1/8"-8	22.75	13.39	1.42	16.61	6.89	4	0.70	5.51	1.063	0.55	F14	-	234
20	5.00	20	1-1/8"-8	25.00	14.37	1.42	17.91	8.27	4	0.87	6.50	1.417	0.60	F16	-	268
24	6.06	20	1-1/4"-8	29.50	17.80	1.81	22.24	8.27	4	0.87	6.50	1.417	0.60	F16	-	520

DESCRIPTION:
 2"-24" API 609, 150# Lug Body, Bare Shaft
 Resilient Seated BFV

DATE:
 08/13/2024

DRAWING:
 TS-DD0001-B



McWane Plant & Industrial
 1201 Vanderbilt Road
 Birmingham, AL 35234