



DIMENSIONS (Inches)																				
SIZE	A	B	C	D	E	F	G	V	W	X	AA	BB	CC	DD	EE	HH	WT (lbs)	ACT. MODEL	TURNS TO OPEN	
3	5.00	1.12	8.25	8	0.88	6.63	4.13	-	-	8.13	1.63	8.13	5.56	3.06	3.69	10.00	67	450	29	
4	5.00	1.25	10.00	8	0.88	7.88	5.00	-	-	8.93	1.63	8.13	5.56	3.06	3.69	10.80	86	450	29	
6	6.00	1.44	12.50	12	0.88	10.63	6.25	-	-	10.63	1.63	8.13	5.56	3.06	3.69	12.50	119	450	29	
8	8.00	1.62	15.00	12	1.00	13.00	7.50	-	-	11.32	1.63	8.13	5.56	3.06	3.69	13.20	169	450	29	
10	8.00	1.88	17.50	12	1.13	15.25	8.75	4	1 1/8"-7	11.88	13.03	1.63	8.13	5.56	3.06	3.69	14.90	224	450	29
12	8.00	2.00	20.50	12	1.25	17.75	9.50	4	1 1/8"-7	12.00	14.23	1.63	8.13	5.56	3.06	3.69	16.10	277	450	29
14	12.00	2.12	23.00	16	1.25	20.25	11.50	4	1 1/8"-7	12.12	17.40	4.00	11.88	8.38	4.13	7.88	20.34	544	1250	48
16	12.00	2.25	25.50	16	1.38	22.50	12.75	4	1 1/4"-7	12.25	18.60	4.00	11.88	8.38	4.13	7.88	21.54	647	1250	48
18	12.00	2.38	28.00	20	1.38	24.75	14.00	4	1 1/4"-7	12.38	20.00	4.00	11.88	8.38	4.13	7.88	22.94	771	1250	48
20	12.00	2.50	30.50	20	1.38	27.00	15.25	4	1 1/4"-7	12.50	20.50	4.00	11.88	8.38	4.13	7.88	23.44	939	1250	48
24	12.00	2.75	36.00	20	1.63	32.00	20.00	4	1 1/2"-6	12.95	22.50	6.00	13.88	10.38	5.90	10.75	25.44	1,397	2200	72

NOTE:

1. FLANGES CONFORM TO ANSI B16.1 CLASS 250
2. COLD WORKING PRESSURE = 250PSI
3. HYDROSTATIC TEST PRESSURE = 500PSI

DESCRIPTION:

3"-24" AWWA 250B - 250# FLG BFV w/
Buried Service TNA (Seat on Body - 4700)

DATE:

07/01/24

DRAWING:

BF-DD0010-A



McWane Plant & Industrial
1201 Vanderbilt Road
Birmingham, AL 35234

