



**DIMENSIONS (Inches)**

SIZE	A	B	C	D	E	F	G	V	W	X	AA	BB	CC	DD	HH	WT (lbs)	ACT. MODEL	TURNS TO OPEN	
30	12.00	3.00	43.00	24	2.00	39.25	24.00	4	1 3/4"-5	12.75	27.52	2.85	14.36	5.61	9.09	31.26	1,756	IW5/IR1	24
36	15.00	3.38	50.00	24	2.25	46.00	27.28	8	2"-4.5	12.95	31.50	4.50	14.36	7.38	10.74	35.24	2,827	IW6/IR1	57

- NOTE:**
1. FLANGES CONFORM TO ANSI B16.1 CLASS 250
  2. COLD WORKING PRESSURE = 250PSI
  3. HYDROSTATIC TEST PRESSURE = 500PSI

<b>DESCRIPTION:</b> 30"-36" AWWA 250B - 250# FLG BFV w/ Buried Service WGA (Seat on Body - 4700)	<b>DATE:</b> 07/01/2024	<b>DRAWING:</b> BF-DD0012-A
--------------------------------------------------------------------------------------------------------	----------------------------	--------------------------------

**MPI MCWANE** PLANT & INDUSTRIAL  
 McWane Plant & Industrial  
 1201 Vanderbilt Road  
 Birmingham, AL 35234

**CLOW** VALVE CO.  
 KENNEDY VALVE  
 M&H VALVE COMPANY