



DIMENSIONS (Inches)

SIZE	A	D	E	F	G	H	J	K	L	WT (lbs.)
2	1.70	4	5/8"-11 UNC-2B	4.75	3.15	1.10	6.61	2.46	10.24	9.7
2.5	1.81	4	5/8"-11 UNC-2B	5.50	3.50	1.10	7.00	2.46	10.24	10.8
3	1.81	4	5/8"-11 UNC-2B	6.00	3.74	1.10	7.32	2.46	10.24	12.4
4	2.05	8	5/8"-11 UNC-2B	7.50	4.49	1.10	8.03	2.46	10.24	18.5
5	2.20	8	3/4"-10 UNC-2B	8.50	5.00	1.10	8.58	2.46	10.24	23.6
6	2.20	8	3/4"-10 UNC-2B	9.50	5.47	1.10	9.45	2.46	10.24	26.9
8	2.36	8	3/4"-10 UNC-2B	11.75	6.89	1.38	10.63	3.47	14.17	48.7
10	2.68	12	7/8"-9 UNC-2B	14.25	7.99	1.38	11.81	3.47	14.17	73.0

DESCRIPTION:
2"-12" API 609, 150# Lug Body Resilient Seated
BFV w/ Lever Operator

DATE:
05/31/2024

DRAWING:
TS-DD0002-A



McWane Plant & Industrial
1201 Vanderbilt Road
Birmingham, AL 35234