



DIMENSIONS (Inches)

SIZE	A	B	C	D	E	F	H	WT (lbs)
3	13.00	1.00	9.00	4	SEE NOTE	6.00	6.78	71
4	13.00	1.00	9.00	8	0.75	7.50	6.78	71
6	16.00	1.06	11.00	8	0.88	9.50	9.29	118
8	19.50	1.19	13.50	8	0.88	11.75	10.84	185
10	24.50	1.25	16.00	12	1.00	14.25	13.23	295
12	27.50	1.28	19.00	12	1.00	17.00	15.29	391
14	31.00	1.00	21.00	12	1.13	18.75	18.00	648
16	32.00	1.13	23.50	16	1.13	21.25	18.93	780
18	36.00	1.38	25.00	16	1.25	22.75	22.03	1,093
20	40.00	1.38	27.50	20	1.25	25.00	23.28	1,402
24	48.00	1.50	32.00	20	1.38	29.50	27.63	2,097
30	56.00	2.12	38.75	28	1.38	36.00	34.90	3,880
36	63.00	2.38	46.00	32	1.63	42.75	38.43	5,744

NOTE:

1. 3" VALVE FLANGES DRILLED & TAPPED TO 5/8"-11 UNC-2B
2. COLD WORKING PRESSURE - 250PSI
3. HYDROSTATIC TEST PRESSURE - 500PSI

DESCRIPTION:

3"-36" 125# Flanged KEN-FLEX™ Check Valve

DATE:

02/27/2026

DRAWING:

KF-DD0001-A



McWane Plant & Industrial
1201 Vanderbilt Road
Birmingham, AL 35234

CLOW
VALVE CO.

