



DIMENSIONS (Inches)

SIZE	A	B	C	D	E	F	H	J	WT (lbs)
3	13.00	1.00	9.00	4	SEE NOTE	6.00	6.78	12.21	74
4	13.00	1.00	9.00	8	0.75	7.50	6.78	12.21	74
6	16.00	1.06	11.00	8	0.88	9.50	9.29	14.28	121
8	19.50	1.19	13.50	8	0.88	11.75	10.84	15.60	188
10	24.50	1.25	16.00	12	1.00	14.25	13.23	17.04	298
12	27.50	1.28	19.00	12	1.00	17.00	15.29	18.45	394
14	31.00	1.00	21.00	12	1.13	18.75	18.00	25.20	653
16	32.00	1.13	23.50	16	1.13	21.25	18.93	25.60	785
18	36.00	1.38	25.00	16	1.25	22.75	22.03	27.70	1,098
20	40.00	1.38	27.50	20	1.25	25.00	23.28	28.90	1,407
24	48.00	1.50	32.00	20	1.38	29.50	27.63	31.60	2,102
30	56.00	2.12	38.75	28	1.38	36.00	34.90	42.30	3,887
36	63.00	2.38	46.00	32	1.63	42.75	38.43	46.00	5,751

- NOTE:
- 3" VALVE FLANGES DRILLED & TAPPED TO 5/8"-11 UNC-2B
 - COLD WORKING PRESSURE - 250PSI
 - HYDROSTATIC TEST PRESSURE - 500PSI

DESCRIPTION:

3"-36" 125# Flanged KEN-FLEX™ Check Valve w/ Position Indicator

DATE:

02/27/2026

DRAWING:

KF-DD0003-A



McWane Plant & Industrial
1201 Vanderbilt Road
Birmingham, AL 35234

CLOW
VALVE CO.

