



No.	PART	MATERIAL
1	Body	Ductile Iron, ASTM A536 - GR 65-45-12
2	Body Seat	EPDM
3	Disc*	Ductile Iron, ASTM A536 - GR 65-45-12
4	Disc Edge	Stainless Steel, T316
5	Stem	150B - Stainless Steel, T316 250B - Stainless Steel, T630
6	V-Packing	EPDM
7	Bearing	Teflon-Lined; Fiberglass Backed
8	Taper Pin	Stainless Steel, T630
9	Taper Pin O-Ring	EPDM
10	Hex Nut	Stainless Steel, T316
11	Washer	Stainless Steel, T316
12	O-Ring (3"-8") V-Packing (10"-24")	EPDM
13	End Cap	Carbon Steel, #45
14	Hex Bolt	Stainless Steel, T316
15	Packing Retainer Screw	Stainless Steel, T316
16	Gland	Stainless Steel, T304

*Stainless Steel, T316 for 3" Valve Size

DESCRIPTION: 3"-24" AWWA Butterfly Valve Materials of Construction (Seat on Body) - Below Ground	DATE: 07/01/24	DRAWING: BF-MC0002-A
--	--------------------------	--------------------------------

MPI MCWANE PLANT & INDUSTRIAL
 McWane Plant & Industrial
 1201 Vanderbilt Road
 Birmingham, AL 35234