



No.	PART	MATERIAL
1	Body	Carbon Steel, ASTM A216 - GR WCB, or
		Stainless Steel, ASTM A351 - GR CF8M
2	Retainer Ring	Carbon Steel, ASTM A216 - GR WCB, or
		Stainless Steel, ASTM A351 - GR CF8M
3	Disc	Stainless Steel, ASTM A351 - GR CF8M
4	Seat	MPTFE
5	Stem	Stainless Steel, ASTM A564 - T630
6	V-Packing	PTFE
7	Bushing	Stainless Steel Backed RTFE
8	Taper Pin	Stainless Steel, ASTM A182 - T316
9	Gland Bushing	Stainless Steel, ASTM A351 - GR CF8M
10	Gland Flange	Stainless Steel, ASTM A351 - GR CF8M
11	Anti-Blowout Pin	Stainless Steel, ASTM A182 - T316
12	Thrust Bearing	PTFE
13	Thrust Ring	Stainless Steel, ASTM A351 - GR CF8M
14	Gasket	PTFE
15	End Plate	Carbon Steel, ASTM A216 - GR WCB, or
		Stainless Steel, ASTM A351 - GR CF8M
16	Hardware	Stainless Steel, ASTM A182 - T316

<b>DESCRIPTION:</b> 2"-36" API 609 High Performance Butterfly Valve Materials of Construction	<b>DATE:</b> 09/02/24	<b>DRAWING:</b> TS-MC0004-A
---	--------------------------	--------------------------------

**MPI MCWANE** PLANT & INDUSTRIAL  
 McWane Plant & Industrial  
 1201 Vanderbilt Road  
 Birmingham, AL 35234