





No.	PART	MATERIAL
1	Body	Ductile Iron, ASTM A536 - GR 65-45-12 with Welded Nickel Seat
2	Cover	Ductile Iron, ASTM A536 - GR 65-45-12
3	Plug	Ductile Iron, ASTM A536 - GR 65-45-12 with NBR (Buna-N) Plug Facing
4	Follower Gland	Ductile Iron, ASTM A536 - GR 65-45-12
5	Grit Seal	NBR (Buna-N)
6	V-Packing	NBR (Buna-N)
7	Sleeve Bearing	Sintered Stainless Steel, T316
8	Thrust Bearing	PTFE
9	Cover Seal	NBR (Buna-N)
10	Cover Hardware	Stainless Steel, T316 - ASTM A276
11	Stud	Stainless Steel, T316 - ASTM A276
12	Hex Nut	Stainless Steel, T316 - ASTM A276
13	Mounting Bracket	Ductile Iron, ASTM A536 - GR 65-45-12
14	Bracket Hardware	Stainless Steel, T316 - ASTM A276

DESCRIPTION: 3"-24" AWWA C517 Eccentric Plug Valve Materials of Construction	DATE: 08/01/24	DRAWING: EP-MC0002-A	  
			


 McWane Plant & Industrial
 1201 Vanderbilt Road
 Birmingham, AL 35234