



**DIMENSIONS (Inches)**

SIZE	A	B	C	D	E	F	GG	HH OPEN	HH CLOSED	WT (lbs)	TURNS TO OPEN
3	8.00	0.75	7.50	4	0.75	6.00	10.00	18.88	15.63	68	10
4	9.00	0.94	9.00	8	0.75	7.50	10.00	22.75	18.25	92	13
6	10.50	1.00	11.00	8	0.88	9.50	12.00	30.13	23.75	141	19
8	11.50	1.13	13.50	8	0.88	11.75	14.00	37.75	29.25	213	25
10	13.00	1.19	16.00	12	1.00	14.25	18.00	45.75	35.38	369	31
12	14.00	1.25	19.00	12	1.00	17.00	18.00	53.13	40.63	480	37
14	15.00	1.38	21.00	12	1.13	18.75	22.00	77.32	60.69	670	52
16	16.00	1.44	23.50	16	1.13	21.25	22.00	76.30	59.73	735	52

**NOTE:**

1. FLANGES CONFORM TO ANSI B16.1 CLASS 125
2. COLD WORKING PRESSURE - 250PSI
3. HYDROSTATIC TEST PRESSURE - 500PSI

**DESCRIPTION:**

3"-16" AWWA C515 - 125# FLG x FLG  
Resilient Wedge Gate Valve (OS&Y)

**DATE:**

02/28/2026

**DRAWING:**

RW-DD0011-A



McWane Plant & Industrial  
1201 Vanderbilt Road  
Birmingham, AL 35234

