



No.	PART	STANDARD MATERIAL	OPTIONAL MATERIAL
1	Body	Ductile Iron, ASTM A536	-
2	Bonnet	Ductile Iron, ASTM A536	-
3	Wedge	EPDM Encapsulated Ductile Iron, ASTM A536	-
4	Stem Nut	Silicon Bronze, C87850	C87610, C87845, C89833, C99500
5	Stem	Stainless Steel, T304	C65500, Stainless Steel, T316
6	Stem O-ring	NBR	EPDM
7	Bonnet O-ring	NBR	EPDM
8	Bonnet Hardware	Stainless Steel, 18-8	Stainless Steel, T316
9	Thrust Washer	Delrin/Nylatron	-
10	Handwheel	Ductile Iron, ASTM A536	-
30	Yoke Nut	Manganese Bronze, C86700	-
31	Yoke Nut Washer	Bronze, C26000	-
34	Wheel Nut	Bronze, C87850	C87610
35	Pin	Stainless Steel, T303	-
41	Packing	Garlock Style 18	-
42	Gland	Ductile Iron, ASTM A536	-
44	Gland Hardware	Stainless Steel, 18-8	Stainless Steel, T316

<b>DESCRIPTION:</b> 3"-12" Resilient Seated Gate Valve - No Gear Materials of Construction (OS&Y)	<b>DATE:</b> 03/06/2026	<b>DRAWING:</b> RW-MC0002-A
---	----------------------------	--------------------------------


 McWane Plant & Industrial  
 1201 Vanderbilt Road  
 Birmingham, AL 35234

  
  


Products and images depicted are for general illustrative purposes only and do not represent the complete scope of supply, configuration, or country of origin. Final product details are governed solely by McWane Plant & Industrial's standard Terms and Conditions of Sale.