



DIMENSIONS (Inches)

SIZE	A	B	C	D	E	F	G	H	H2	J	L	L2	S	X	WT (lbs)
3	9.50	0.78	7.50	4	0.75	6.00	-	6.85	8.81	7.50	5.69	5.69	0.50	6.00	57
4	11.50	1.00	9.00	8	0.75	7.50	-	8.69	10.38	9.00	8.25	8.25	0.63	7.75	99
6	14.00	1.06	11.00	8	0.88	9.50	-	10.51	13.31	11.00	9.31	9.31	0.75	9.75	150
8	19.50	1.25	13.50	8	0.88	11.75	-	12.56	18.80	13.50	10.00	10.00	0.88	14.13	320
10	24.50	1.31	16.00	12	1.00	14.25	-	14.07	23.38	16.75	11.63	11.63	1.00	18.00	474
12	27.50	1.38	19.00	12	1.00	17.00	-	16.13	24.38	19.00	14.38	14.38	1.00	18.00	686
14	31.00	1.38	21.00	12	1.12	18.75	10.75	15.97	24.50	22.38	18.58	18.58	1.25	14.81	695
16	36.00	1.44	23.50	16	1.12	21.25	11.75	18.88	26.25	25.75	19.44	19.44	1.50	14.81	908
18	40.00	1.56	25.00	16	1.25	22.75	12.63	20.30	27.94	28.25	19.38	19.38	1.75	15.45	1,114
20	40.00	1.69	27.50	20	1.25	25.00	14.00	20.63	28.50	30.50	20.00	20.00	1.75	15.45	1,351
24	48.00	1.88	32.00	20	1.38	29.50	17.50	24.25	31.06	34.88	23.75	23.75	2.00	15.45	1,847
30	56.00	2.13	38.75	28	1.38	36.00	19.63	29.88	34.38	41.00	26.00	26.00	2.00	15.45	3,439

NOTE:

1. FLANGES CONFORM TO ANSI B16.1 CLASS 125
2. COLD WORKING PRESSURE
3"-12" - 250 PSI, 14"-36" - 150 PSI
3. HYDROSTATIC TEST PRESSURE
3"-12" - 500 PSI, 14"-36" - 300 PSI

DESCRIPTION:

3"-30" AWWA C508 - 125# Flanged Swing Check Valve with Dual Lever & Spring (3306)

DATE:

01/15/2025

DRAWING:

SW-DD0006-A



McWane Plant & Industrial
1201 Vanderbilt Road
Birmingham, AL 35234