

F-55D FLAP GATE



- SIZES 6" TO 108"
- HEAVY DUTY DUCTILE IRON
- RATED FOR UP TO 55 FEET OF SEATING HEAD

MARKETS



AGRICULTURE



CIVIL



WATER/
WASTEWATER

SPECIFICATIONS

Size Range	6"-108"
Seat Angle	2.5°
Mounting	125# flange mount or wall mount
Flange Drilling	ANSI/AWWA C110, C111 (125# standard)
Assembly Hardware	Stainless steel per ASTM F593, Type 304 or Type 316 optional
Seating Head	Up to 55 feet
Frame & Cover Materials	ASTM A536 ductile iron
Seat Materials	Ductile iron per ASTM A-536 or naval bronze per ASTM B21 Alloy C48200 or neoprene per ASTM D2000 BC 60 Shore
Hinge Pin & Hinge Link	Stainless steel per ASTM A-276, Type 304 standard or Type 316
Hinge Bushings	SAE 30 oil-embedded bronze bearings



FEATURES AND BENEFITS

1. Engineered for Durability

Our frame and cover are precision-crafted from high-strength ductile iron, delivering the rugged durability of steel with the versatility and flexibility of cast iron. Compared to traditional grey iron, ductile iron has increased yield strength and tensile strength to improve cracking resistance and impact absorption, ensuring reliable performance even under extreme stress. Whether you're operating in high cycle applications or corrosive environments this material choice means less downtime, fewer replacements, lower total cost of ownership and long-term peace of mind.



2. Smooth, Silent, and Built to Last

To ensure long-term reliability and quiet operation, the hinge bushing features oil-embedded bearing bronze, a premium material known for its exceptional wear and corrosion resistance. This advanced design minimizes friction, reduces maintenance, and extends the service life of the flap gate, even in the most demanding environments.

3. Bronze Seals: The Superior Solution for Corrosive Environments

Bronze's exceptional resistance to corrosion, especially from saltwater, chemicals, and acidic conditions, ensures that the seal maintains its integrity and functionality over time, even under constant exposure to harsh elements. Unlike rubber or steel alternatives that may degrade, swell, or rust, bronze offers a stable, low-maintenance solution that supports smooth gate operation and tight sealing. This durability translates into reduced downtime, fewer replacements, and lower lifecycle costs, making bronze seals a smart investment for critical water control infrastructure in corrosive settings.

4. Precision That Performs: The 2.5° Seat Angle Advantage

When it comes to water control, every detail matters. This subtle design feature ensures positive closure by harnessing gravity and flow dynamics to guide the gate into a secure, leak-resistant seal every time. Whether facing fluctuating water levels or debris-laden flows, the angled design promotes consistent performance, reducing the need for manual adjustments or costly maintenance. It's a small angle with a big impact, delivering confidence and reliability in every application.



5. Pump Discharge Applications: The Secret Formula

Our pump discharge solution combines a spring bumper, neoprene seal, and 125-pound flange to deliver unmatched reliability. The spring bumper cushions for reduced wear and prevents the flap from over-extending, while the neoprene seal ensures a tight, flexible barrier against backflow. Anchored by a heavy-duty flange to mount directly to a pipe flange, this system is built to handle pressure, vibration, and corrosive conditions maximizing uptime and minimizing maintenance.



This document is provided for general informational purposes only and is not intended to define or represent the scope of supply, configuration, or origin of any product. Images, drawings, diagrams, photographs, and specifications may depict optional features or representative designs and are subject to change without notice. Nothing contained herein shall be deemed to create or extend any warranty, express or implied. All products are sold subject exclusively to McWane Plant & Industrial's standard Terms and Conditions of Sale.



MPI - MCWANE PLANT & INDUSTRIAL
1201 Vanderbilt Road, Birmingham, AL 35234
866.924.8674 • mcwanepi.com • sales@mcwanepi.com

BR-F55D-2 3/26