



Electric Motor Operator Options for Ordering

Contact Information

Job Name: _____ Job number: _____

Contact Name: _____ Phone number: _____

Email Address: _____

Manufacturer Preference:

☐ AUMA ☐ Limitorque ☐ Rotork ☐ EIM

Service:

- ☐ Open/Close
☐ Moderate Modulating - 25% Duty Cycle
☐ Continuous Modulating - 50% Duty Cycle

Power Supply Voltage:

☐ 460/480 ☐ 230/240 Three phase ☐ 120/110 Single phase

Power Supply Frequency:

☐ 60 Hertz ☐ 50 Hertz ☐ DC Voltage: _____
☐ Other: _____

Controls:

- ☐ Local Push Button ☐ Remote Push Button
☐ Remote Signal Output ☐ Remote Signal Input (4-20mA)
☐ Remote Signal Readout ☐ Alarm Output

Motor Operator Enclosure Type:

☐ Nema 7 ☐ Nema 4 ☐ IP67
☐ IP68 ☐ Other: _____

Motor Operator Enclosure:

☐ Submerged ☐ Non-Submerged

Gate Speed:

☐ 10-14 Inches/Minute ☐ Other _____

Handwheel Position:

☐ Side ☐ Top

Handwheel Direction to Open Gate:

☐ Clockwise / Right Hand ☐ Counter-Clockwise/Left Hand

Motor Operator Finish:

☐ Standard Duty Finish ☐ Corrosive Duty Finish

If you are retrofitting an existing gate, we also need the following information:

Primary Material Type: _____

Gate Size (Width, Height): _____

Fluid Head:

☐ Seating _____ ☐ Unseating _____
☐ Differential _____

Stem Length:

Distance from operator mount to thrust nut: _____

Stem Diameter: _____

Factory Start Up:

☐ Yes ☐ No

Seat Type (Friction Factor): _____

Seat Type:

☐ UHMW ☐ Bronze ☐ Metal to Metal ☐ J-Bulb

Mounting:

☐ Headrail ☐ Pedestal

